



Cable Ties and Accessories

Installation Cable Ties CCL



www.mecatraccion.com

SICAME GROUP

Features

- CCL Series cable ties, UV resistant, are particularly adapted for outdoor installation of electrical application but can be used for indoor installation.
- Material : PA6
- Halogen free
- Good resistance to UV
- Operating temperature: -40°C / +70°C
- Melting temperature: 120 °C
- Flammability rating: UL94V2
- Resistance to external agents :
 - Insensitivity to motors oils, greases, petroleum products
 - Good resistance to bases and chlorinated solvents
 - Limited resistance to acids
 - Non resistant to phenols



Specifications

Designation	Part number	Length L (mm)	Width W (mm)	Ø Max Bundle (mm)	Mini strength (daN)	Packaging
Single locking						
CCL9-180	7100055	180	9	40	35	100 pcs
Double locking						
CCL9-265	7100056	265	9	63	54	100 pcs
CCL9-360	7100057	360	9	92	54	100 pcs
CCL9-510	7100058	510	9	142	54	100 pcs
CCL9-760	7100059	760	9	214	54	100 pcs

Accessories

Designation	Part number	Material	Packaging	Type
SERCOL	7500311	Steel	1 pcs	Hand tool for installation cable ties from 6 to 9 mm width
CH8P	7100113	PA6	100 pcs	Cable ties supports Ø8mm with 6mm spacing
CHEM8	7100111	PA12	100 pcs	Cable ties supports Ø8mm with 12mm spacing
EM7	7100101	PA12	100 pcs	Screw-fitted supports with gland stud Ø7mm or countersunk screw Ø5mm
EM7P	7100102	PA6	100 pcs	Screw-fitted supports with gland stud Ø7mm or countersunk screw Ø5mm



SERCOL



EM7 – EM7P



CHEM8 – CH8P



MECATRACTION
 ZA Les Hauts de Chignac – 19230 POMPADOUR – France
 Phone : +33(0)5 55 73 89 89 - Fax : +33(0)5 55 73 32 21
 E-mail : info@mecatraction.com
www.mecatraction.com